

1. Introduction

HANWHA P-1000 is a PVC homopolymer made by suspension polymerization. It is recommended for various products such as pipe, sheet, profile, wire, film manufacturing. P-1000 is a general purpose resin used for soft and rigid applications and is most widely used in PVC grades.

2. Applications

Pipe, Window profile, Wire sheath, Soft/Rigid sheet & film, Hose, Leather, Wrap

3. Properties

Properties	Methods	Unit	Typical value
Degree of polymerization	JIS K6720-2	-	1000±50
K-Value	DIN 53726	-	66
Apparent bulk density	ASTM D1895	g/cm ³	0.55±0.04
Volatility	ASTM D3030	%	Below 0.30
Sieve analysis (42mesh pass)	HCC method	%	100

*The values given above are typical test results which should be used as a guide only. They do not form the whole or part of a specification or guarantee.

4. Storage, Packaging, Safety

Storage

P-1000 should be stored dry conditions and at room temperature below 25°C.

Safety and Handling

The Hanwha Chemical Corporation provides its customers with a product specific Material Safety Data Sheet (MSDS) to cover potential health effects, safe handling, use and transportation. Hanwha Chemical Corporation strongly encourage its customers to review MSDS on its products and other materials prior to their use. P-1000 is normally supplied as a power in 25kg polypropylene inner coated paper bag, 500kg flecon bag as well as in bulk form.

P-1000 is not formulated to contain any hazardous or regulated materials such as lead,